

## "The Professional's Industry Standard Tree Stake"

EASY Installation (Screws into Ground)

 VANDAL & THEFT Resistant

· REUSABLE

• ENVIRONMENTALLY Friendly

> For 36" and 48" Box Trees

## "Only One Stake Needed Per Tree"



**209.634.7791** sales@JRPartnersCo.com www.TreeStake.com



## Mega Tree Stake (Patent # 6,702,239 B2) (For 36" & 48" Box Trees) Single Tree Staking System:

**"Mega Stake System"**; a screw in auger-type steel stake with an adjustable anti-rotational tab and pin device, adjustable height strap-bar, UV-resistant adjustable vinyl strap with 2 bolts/washers/nuts and powder-coated black.

## Specifications

The Mega Stake shall be utilized for tree sizes **36" and 48" box trees**. It shall be a minimum of 11 feet in length with an outside diameter of 1.66" and .14" wall thickness. Each stake shall have an anti-adjustable height anti-rotational device (tab/pin) with a yellow indicator line placed at 36" from the bottom of the stake for the recommended minimum installation depth. Each steel tree stake shall have a solid plug welded in top end of stake. All steel tree stakes shall have a powder coated baked on finish for rust inhibiting qualities.

Each steel tree stake shall be tied with a minimum of one strapping-bar. The strap-bar shall be installed at the lowest position, which supports the tree in an upright position. Each strap-bar shall consist of an 3/8" x 18" flat bar secured with two set bolts and utilizing a strap with a minimum of  $\frac{1}{4}$ " x 1" x 20" 90 Duro Flex PVC with UV inhibitors; secured in place with a minimum of (2)  $\frac{1}{4}$ " x 1  $\frac{3}{4}$ " bolts/washers/nuts.

Trees to be staked shall be staked at the time of planting as shown on the plans or specified in the special provisions. One steel tree stake shall be installed 18 to 24 inches away on the prevailing wind side of the tree. The steel tree stake should be installed to a minimum of 36" below finished grade.

